ECODESIGN INFORMATION

www.sodeca.com

According to Regulation EU No 2024/1834 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SODECA, S.L.U.

a) fan type
b) fan efficiency [%]
c) VSD assumed in data
d) Measurement category
e) Efficiency category
f) N fan
g1) Pe [kW]
g2) qv [m³/h]
g3) Δp [Pa]
h1) dual use fan
h2) reversible fan
h3) low noise fan
i) DC voltage lower than 100 V
k) σBEP
l) fan speed [rpm]
m) specific ratio
j) p) q) significant elements, disassembly and recycling info on product manual

Model	a)	b)	c)	d)	e)	f)	g1)	g2)	g3)	h1)	h2)	h3)	i)	k)	l)	m)
CMPH-512-2T-0.25	*Exclude. Gas Temp> 100°C*															
CMPH-512-4T-0.16	*Exclude. Gas Temp> 100°C*															
CMPH-514-2T-0.25	*Exclude. Gas Temp> 100°C*															
CMPH-514-4T-0.16	*Exclude. Gas Temp> 100°C*															
CMPH-616-2T-0.5	*Exclude. Gas Temp> 100°C*															
CMPH-616-4T-0.16	*Exclude. Gas Temp> 100°C*															
CMPH-620-2T-0.5	*Exclude. Gas Temp> 100°C*															
CMPH-620-4T-0.16	*Exclude. Gas Temp> 100°C*															
CMPH-718-2T-1 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-718-4T-0.33	*Exclude. Gas Temp> 100°C*															
CMPH-820-2T-1.5 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-820-4T-0.33	*Exclude. Gas Temp> 100°C*															
CMPH-922-2T-1.5 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-922-2T-2 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-922-2T-3 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-922-4T-0.75	*Exclude. Gas Temp> 100°C*															
CMPH-1025-2T-3 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1025-2T-4 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1025-4T-1.5 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1128-2T-4 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1128-2T-5.5 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1128-4T-3 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1128-6T-1 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1231-4T-3 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1231-4T-4 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1231-4T-5.5 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1231-6T-2 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1435-4T-4 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1435-4T-5.5 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1435-4T-7.5 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1435-6T-3 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1640-4T-5.5 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1640-4T-7.5 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1640-4T-10 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1640-6T-3 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1845-4T-7.5 IE3	*Exclude. Gas Temp> 100°C*															

ECODESIGN INFORMATION

According to Regulation EU No 2024/1834 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SODECA, S.L.U.

Model	a)	b)	c)	d)	e)	f)	g1)	g2)	g3)	h1)	h2)	h3)	i)	k)	l)	m)
CMPH-1845-4T-10 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-1845-6T-3 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-2050-4T-10 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-2050-4T-15 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-2050-4T-20 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-2050-6T-5.5 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-2563-6T-15 IE3	*Exclude. Gas Temp> 100°C*															
CMPH-2563-6T-25 IE3	*Exclude. Gas Temp> 100°C*															