

ECODESIGN INFORMATION

According to Regulation EU No 2024/1834 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SODECA, S.L.U.

- a) fan type

b) fan efficiency [%]

c) VSD assumed in data

d) Measurement category
- e) Efficiency category

f) N fan

g1) Pe [kW]

g2) qv [m³/h]
- g3) Δp [Pa]

h1) dual use fan

h2) reversible fan

h3) low noise fan
- i) DC voltage lower than 100 V

k) σBEP

l) fan speed [rpm]

m) specific ratio
- j) p) q) significant elements, disassembly and recycling info on product manual

Model	a)	b)	c)	d)	e)	f)	g1)	g2)	g3)	h1)	h2)	h3)	i)	k)	l)	m)
HBA-31-2T-0.75									Exclude. Gas Temp> 100°C							
HBA-31-2M-0.75									Exclude. Gas Temp> 100°C							
HBA-31-4T-0.37									Exclude. Gas Temp> 100°C							
HBA-31-4M-0.37									Exclude. Gas Temp> 100°C							
HBA-40-2T-1.5 IE3									Exclude. Gas Temp> 100°C							
HBA-40-2M-1.5									Exclude. Gas Temp> 100°C							
HBA-40-4T-0.5									Exclude. Gas Temp> 100°C							
HBA-45-2T-4 IE3									Exclude. Gas Temp> 100°C							
HBA-50-4T-1 IE3									Exclude. Gas Temp> 100°C							
HBA-63-4T-1.5 IE3									Exclude. Gas Temp> 100°C							
HBA-71-4T-5.5 IE3									Exclude. Gas Temp> 100°C							
HBA-71-6T-0.75									Exclude. Gas Temp> 100°C							
HBA-80-6T-1.5 IE3									Exclude. Gas Temp> 100°C							
HBA-100-6T-1.5 IE3									Exclude. Gas Temp> 100°C							