

# ECODESIGN INFORMATION

Applies to residential ventilation units (RVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

a) Brand	SODECA, SLU	SODECA, SLU	SODECA, SLU	SODECA, SLU	SODECA, SLU
b) Model	NEOLINEO/EW-100	NEOLINEO/EW-125	NEOLINEO/EW-150	NEOLINEO/EW-160	NEOLINEO/EW-200
c) Specific energy consumption (SEC) average climate (kWh/(m <sup>2</sup> .yr))	-26.9	-27.4	-27.5	-27.5	-27.1
c) Specific energy consumption (SEC) cold climate (kWh/(m <sup>2</sup> .yr))	-53.9	-54.5	-54.6	-54.6	-54.1
c) Specific energy consumption (SEC) warm climate (kWh/(m <sup>2</sup> .yr))	-11.4	-11.9	-12	-12	-11.6
c) SEC class	B	B	B	B	B
d) Typology	RVU / UVU	RVU / UVU	RVU / UVU	RVU / UVU	RVU / UVU
e) Drive type	Variable speed	Variable speed	Variable speed	Variable speed	Variable speed
f) HRS type	None	None	None	None	None
g) Thermal efficiency of heat recovery (%)					
h) Maximum flow rate (m <sup>3</sup> /h)	200	328	508	508	910
i) Electric power input of the fan drive at maximum flow rate (W)	30	40	54	54	123
j) Sound power level (LWA) (dBA)	67	69	66	66	69
k) Reference flow rate (m <sup>3</sup> /s)	0.039	0.064	0.099	0.099	0.177
l) Reference pressure difference (Pa)	50	50	50	50	50
m) SPI (W/m <sup>3</sup> /h)	0.109	0.068	0.058	0.058	0.094
n) Control factor	0.65	0.65	0.65	0.65	0.65
n) Control typology	Local demand control	Local demand control	Local demand control	Local demand control	Local demand control
o) Declared max. internal leakage rate (%)	0.0	0.0	0.0	0.0	0.0
o) Max. external leakage rate (%)	2.7	2.7	2.7	2.7	2.7
p) Mixing rate	0.00	0.00	0.00	0.00	0.00
q) Position and description of visual filter warning	See manual	See manual	See manual	See manual	See manual
r) Instructions to install regulated grilles	See manual	See manual	See manual	See manual	See manual
s) Website	<a href="http://www.sodeca.com">www.sodeca.com</a>	<a href="http://www.sodeca.com">www.sodeca.com</a>	<a href="http://www.sodeca.com">www.sodeca.com</a>	<a href="http://www.sodeca.com">www.sodeca.com</a>	<a href="http://www.sodeca.com">www.sodeca.com</a>
t) Airflow sensitivity to pressure variations at +20 Pa and -20 Pa	0.00	0.00	0.00	0.00	0.00
u) Indoor/outdoor air tightness	0.00	0.00	0.00	0.00	0.00
v) Annual electricity consumption (AEC) average climate (kWh/yr)	58	36	31	31	50
v) Annual electricity consumption (AEC) warm climate (kWh/yr)	58	36	31	31	50
v) Annual electricity consumption (AEC) cold climate (kWh/yr)	58	36	31	31	50
w) Annual heating saved (AHS) average climate (kWh/yr)	2830	2830	2830	2830	2830
w) Annual heating saved (AHS) warm climate (kWh/yr)	1280	1280	1280	1280	1280
w) Annual heating saved (AHS) cold climate (kWh/yr)	5536	5536	5536	5536	5536
ErP compliance	2018	2018	2018	2018	2018